

RAPTOR[®]

TOUGH PROTECTIVE COATINGS



Products you will need



HOW TO MIX RAPTOR TINTABLE KITS



1
SHAKE
Shake the Raptor Tintable bottle thoroughly.



2
MIX THE 1 BOTTLE KIT
For the 1 Bottle Kit, pour the full contents of the hardener into the Raptor Bottle.



3
MIX THE 4 BOTTLE KIT
For the 4 Bottle Kit, pour Raptor Tintable into a mixing cup, and the hardener in the Raptor coating Bottle.



4
SHAKE AGAIN
Replace lid and shake for 2 mins.



5
ADD TINT
With the tint of your choice, add a maximum of 10% by volume.



6
USE MIXING VESSEL
If tinting outside of the bottle, pour the Raptor into the mixing vessel.



7
POUR HARDENER
Pour the measured hardener into the empty Raptor bottle and shake to remove untinted Raptor excess from the bottle.



8
POUR INTO VESSEL
Pour it back into the mixing vessel.



9
MIX
Mix thoroughly again.



10
SHAKE AGAIN
Pour it back into the bottle, replace the lid and shake.

NOTES: ONLY USE RAPTOR WITH SOLVENT-BASED PAINT (WATER-BASED IS NOT COMPATIBLE). IF GOING TO A DISTRIBUTOR FOR COLOUR, MAKE SURE HE DOESN'T INCLUDE BINDER (FOR MAXIMUM PIGMENT STRENGTH). ALL KITS COME WITH THE CORRECT HARDENER TO RAPTOR RATIO, FOR CORRECT ACTIVATION. CORRECT MEASURING IS CRUCIAL. WE RECOMMEND TINTING OUT OF THE BOTTLE TO ENSURE THOROUGH MIXING.

WWW.RAPTORCOATINGS.COM

U-POL Ltd, 4th Floor, The Grange, 100 High Street, London N14 6BN.
T: +44 (0)20 8492 5900 E: uk.sales@u-pol.com

U-POL TECHNICAL SUPPORT:
+44 (0) 1933 230310