

# RAPTOR®

## TOUGH PROTECTIVE COATINGS

Products you will need



### HOW TO DO A CHASSIS



1

#### SAND

Remove as much rust and debris as possible with a coarse abrasive or grinder.



2

#### DEGREASE

Degrease with a solvent-borne degreaser such as WIPE#6 or System 20.



3

#### APPLY EPOXY PRIMER

U-POL recommends 2-3 coats of Epoxy Primer for a maximum anti-corrosive protection.



4

#### ALLOW FLASH-OFF TIME

Allow 10 mins between coats.



5

#### APPLY RAPTOR

Once cured, apply RAPTOR. You can go wet-on-wet (no sanding) within 1 hour.

### NOTES:

**RAPTOR 4:1 ANTI-CORROSIVE EPOXY PRIMER IS ONLY COMPATIBLE WITH THE INCLUDED RAPTOR 4:1 ANTI-CORROSIVE EPOXY PRIMER HARDENER.**

- 7 DAYS OPEN TIME
- 1L COVERS APPROXIMATELY 60 SQ. FT AT 3MIL.

### TOP TIPS:



Grind or remove any rust with a coarse abrasive or a grinder.



Masking is essential to eliminate the risk of overspray.



RAPTOR Epoxy Primer can be applied with a gun, an aerosol or a roller.



RAPTOR 2K Epoxy Primer in aerosol can be useful for smaller areas.

[WWW.RAPTORCOATINGS.COM](http://WWW.RAPTORCOATINGS.COM)

U-POL Ltd, 4th Floor, The Grange, 100 High Street, London N14 6BN.

T: +44 (0)20 8492 5900 E: uk.sales@u-pol.com

**U-POL TECHNICAL SUPPORT:**

**+44 (0) 1933 230310**